



## GYRONET™ TURBO



### APPLICATIONS

Closed and open-air nurseries  
Intensive field crops  
Overhead cooling  
Roof and tunnel cooling and dust cleaning

### SPECIFICATIONS

- Very robust micro-sprinkler
- Micro-sprinkler, 5 different flow rates: 200, 250, 300, 400, 500 l/h
- Nominal flow rates at 2.2 bar pressure
- Maximum recommended working pressure: 3.0 bar
- Inlet connector: 1/2" threaded male
- The rotor is colored Purple

### FEATURES AND BENEFITS

- Anti-ant mechanism prevents insect penetration into the area of the sprinklers nozzle.
- Sprinkler made of plastic materials resistant to all agrochemicals & weather conditions.
- Specially designed for full coverage irrigation where optimal uniformity distribution of water is required.
- Low bridge "shade", to improve uniformity distribution.
- Can be used in Frost fighting and/or Cooling irrigation systems.
- Long-term reliable service

## PERFORMANCE DATA

MODEL	NOZZLE CODE COLOR	NOZZLE SIZE (MM.)	K	X	MAX. WORKING PRESSURE (BAR)	WETTED DIAMETER (M.) UD 100CM. ABOVE GROUND	SWIVEL (ROTOR) CODE COLOR
200	Yellow	1.89	42.5	0.5	3.0	10.0	Purple
250	Purple	2.14	54.5	0.5	3.0	10.0	Purple
300	Green	2.31	64.1	0.5	3.0	11.5	Purple
400	Blue	2.67	86.8	0.5	3.0	12.0	Purple
500	Brown	3.00	108.5	0.5	3.0	12.5	Purple

## GYRONET™ TURBO

This flow chart will determine the desired product definition.

To determine the desired product definition select one of every set of options displayed on the chart.

