

Mist Guard Cooling

Controls mist for the climate you need



- High-precision temperature and humidity sensors
- Up to 10 valves in sequence
- Misting according to temperature and humidity
- Event logbook

 **NETAFIM™**
GROW MORE WITH LESS

Controls mist for the climate you need

Misting applications

- Up to 10 valves 24VAC OR single valve DC Latch
- Built-in precision temperature and humidity sensors
- Advanced control of Booster Pump and Pressure Relief Valve
- Logs temperature and humidity (min & max), and event logbook

Hardware and Software specifications

- Battery operated 2AA Alkaline for DC Latch Solenoid
- Requires 24VAC/1Amp power supply for 10 outputs
- High-precision temperature sensor -50°C (-58°F) to +50°C (122°F), $\pm 0.25^{\circ}\text{C}$ ($\pm 0.45^{\circ}\text{F}$)
- High-precision humidity sensor 0-100%, $\pm 2\%$
- Logs min and max temperature and humidity levels over the last 24-hours
- 480-events logbook includes time and date stamping
- Displays Celsius, Fahrenheit, Relative Humidity and Dew Point readings

Two misting methods:

- Dual-Mist above temperature or below humidity thresholds.
- Heat-Mist above dynamic temperature influenced by humidity

