



MISTNET™

APPLICATIONS:

Fine static mister especially designed for under canopy cooling and humidifying greenhouses and for irrigating over rooting tables

SPECIFICATIONS:

- Bridgeless design eliminates dripping.
- Static mister, 2 flow rates: 15, 25 l/h
Nominal flow rates at 2.7 bar pressure
- Pressure range 2.5 to 5.0 bar
- Inlet connectors:
Press fit
- the nozzles are code color colored:
15.0 l/h. yellow
25.0 l/h. brown

FEATURES AND BENEFITS:

- Bridgeless design eliminates dripping
- Interchangeable components
- Acid resistant (AA) raw materials, thus allowing the application chemicals to pass through the system. The system can be cleaned by application of suitable acid treatments.
- Micro sized droplets, at a relatively low pressure of 4.0 bar the MistNet™ uniformly distributes an average drop size of 150 micron.
- Specially designed for under canopy cooling and humidifying systems

PERFORMANCE DATA

MODEL	NOZZLE CODE COLOR	NOZZLE SIZE DIA. (MM.)	K	X	RECOMMENDED WORKING PRESSURE (BAR)
015	Yellow	1.10	3.30	0.46	3.0
025	Brown	1.30	5.40	0.46	3.0

PACKAGING DATA

MISTNET™	QUANTITY P/BOX UNITS	BOX SIZE CM X CM X CM	BOX WEIGHT KG	BOXES P/PALLET	TOTAL UNITS P/PALLET	PALLET WEIGHT KG.
Head only	5000	18x34x79	21.5	20	100000	430
Complete stand , 60 cm. w/stake	100	18x34x79	5.4	20	2000	119
Complete stand , 60 cm. w/ostake	200	18x34x79	5.1	20	4000	113
Complete stand , 90 cm. w/stake	100	16x35x106	6.4	18	1800	126
Complete stand , 90 cm. w/ostake	150	16x35x106	6.5	18	2700	128

MISTNET™

Flowchart to determine the desired product definition

How to use: To determine the desired product definition select one of every set of options displayed on the chart.

