



DRIPNET PC AS MWD



**COMPACT INTEGRAL PRESSURE COMPENSATING,
CONTINUOUSLY SELF-CLEANING,
ANTI-SIPHON MECHANISM DRIPPER**

**12125 - 12150 - 12200 - 12250 - 16125 - 16150 - 16200
16250 - 22135 - 22150 - 22250 - 25135 - 25150 - 25250**

APPLICATIONS

- Sub-surface multi seasonal row crops.

SPECIFICATIONS

- Pressure-compensating range: 0.25/ 0.40/ 0.60-2.5/ 3.0/ 3.5 bar (according to flow rate model & dripperlines wall-thickness).
- Anti-Siphon mechanism.
- Recommended filtration: according to drippers flow rate.
Filtration method is to be selected based on the kind and concentration of the dirt particles existing in the water. Wherever sand exceeding 2 ppm exists in the water, a Hydrocyclone is to be installed before the main filter. When sand/ silt/ clay solids exceed 100 ppm, pre treatment will be applied according to Netafim™ expert team's instructions.
- TurboNet™ labyrinth with large water passage.
- A wide assortment of dripperlines wall thickness models (0.31, 0.34, 0.38, 0.50, 0.63 mm).
- Injected dripper, very low CV.
- Injected silicon diaphragm.
- UV resistant. Resistant to standard nutrients used in agricultural.
- DripNet PC™ drippers meet ISO 9261 Standards with production certified by the Israel Standards Institute (SII).

FEATURES AND BENEFITS

- Pressure compensated: Precise and equal amounts of water are delivered over a broad pressure range. 100% uniformity of water and nutrient distribution along the laterals.
- Anti-Siphon mechanism: Prevents contaminants from being drawn into the dripper.
- Continuously self flushing: Flushes debris as it is detected, throughout operation, not just at the beginning or end of a cycle, ensuring uninterrupted dripper operation.
- Self-flushing system with wide filtration area improves resistance to clogging.
- TurboNet™ labyrinth assures wide water passages, large deep and wide cross section improves clogging resistance. Widest water passages within the dripper.
- The water is drawn in to the dripper from the stream center, preventing the entrance of sediments in to the drippers.

DRIPPERS TECHNICAL DATA

| FLOW RATE* (L/H) | WORKING PRESSURE RANGE (BAR) | WATER PASSAGES DIMENSIONS WIDTH-DEPTH-LENGTH (MM) | FILTRATION AREA (MM²) | CONSTANT K | EXPONENT* X | RECOMMENDED FILTRATION (MICRON)/(MESH) |
|---------------------|---------------------------------|---|--------------------------|---------------|----------------|---|
| 0.6 | 0.25 - 2.5 | 0.52 x 0.60 x 22 | 42 | 0.6 | 0 | 130/120 |
| 1.0 | 0.40 - 3.0 | 0.61 x 0.60 x 8 | 42 | 1.0 | 0 | 130/120 |
| 1.6 | 0.40 - 3.0 | 0.76 x 0.73 x 8 | 42 | 1.6 | 0 | 200/80 |
| 2.0 | 0.40 - 3.5 | 0.84 x 0.80 x 8 | 42 | 2.0 | 0 | 200/80 |
| 3.0 | 0.40 - 3.5 | 1.02 x 0.88 x 8 | 42 | 3.0 | 0 | 200/80 |
| 3.8 | 0.60 - 3.5 | 1.02 x 0.88 x 8 | 42 | 3.8 | 0 | 200/80 |

* Within working pressure range

NETAFIM AUSTRALIA

P: 1300 307 407
E: au.net.info@netafim.com
W: netafim.com.au



DripNet PC AS MWD Dripperline
September 2017
CP



DRIPNET PC™ AS 12125

Catalog number **17210** - (any of below 6 digits)

| FLOW RATE (L/H) | DISTANCE BETWEEN DRIPPERS (M) | | | | | | | | | | | | | |
|------------------------|-------------------------------|------|------|--------|------|--------|------|------|------|------|------|------|------|------|
| | 0.15 | 0.20 | 0.25 | 0.30 | 0.35 | 0.40 | 0.50 | 0.60 | 0.65 | 0.70 | 0.75 | 0.80 | 0.90 | 1.00 |
| 0.6 | | | | 001370 | | 001470 | | | | | | | | |
| 1.0 | | | | 002470 | | 002570 | | | | | | | | |
| 1.6 | | | | 003470 | | 003570 | | | | | | | | |
| 2.0 | | | | | | | | | | | | | | |
| 3.0 | | | | | | | | | | | | | | |
| 3.8 | | | | | | | | | | | | | | |
| Carton coil length (m) | 900 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 |

Missing catalog numbers available upon request.

DRIPPERLINES TECHNICAL DATA

| MODEL | INSIDE DIAMETER (MM) | WALL THICKNESS (MM) | OUTSIDE DIAMETER (MM) | MAX. WORKING PRESSURE (BAR) | MAXIMUM FLUSHING PRESSURE (BAR) | KD |
|-------|----------------------|---------------------|-----------------------|-----------------------------|---------------------------------|------|
| 12125 | 11.80 | 0.31 | 12.42 | 2.5 | 2.9 | 1.35 |

DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

| MODEL | WALL THICKNESS (MM) | DISTANCE BETWEEN DRIPPERS (M) | COIL LENGTH (M) | AVERAGE* COIL WEIGHT (KG) | COILS PER PALLET (UNITS) | COILS IN A 40 FEET CONTAINER (UNITS) | TOTAL IN A 40 FEET CONTAINER (M) |
|-------|---------------------|-------------------------------|-----------------|---------------------------|--------------------------|--------------------------------------|----------------------------------|
| 12125 | 0.31 | 0.15 to 0.19 | 900 | 14.3 | 12 | 480 | 432000 |
| | | 0.20 to 0.35 | 1000 | 13.6 | | | 480000 |
| | | 0.40 to 1.00 | 1000 | 13.0 | | | 480000 |

*According to drippers spacing

DRIPNET PC™ AS 12150

Catalog number **17225** - (any of below 6 digits)

| FLOW RATE (L/H) | DISTANCE BETWEEN DRIPPERS (M) | | | | | | | | | | | | | |
|------------------------|-------------------------------|------|--------|--------|------|--------|------|------|------|------|------|------|------|------|
| | 0.15 | 0.20 | 0.25 | 0.30 | 0.35 | 0.40 | 0.50 | 0.60 | 0.65 | 0.70 | 0.75 | 0.80 | 0.90 | 1.00 |
| 0.6 | | | 001300 | 001370 | | 001470 | | | | | | | | |
| 1.0 | | | | 002470 | | 002570 | | | | | | | | |
| 1.6 | | | | 003470 | | 003570 | | | | | | | | |
| 2.0 | | | | | | 004610 | | | | | | | | |
| 3.0 | | | | | | | | | | | | | | |
| 3.8 | | | | | | | | | | | | | | |
| Carton coil length (m) | 600 | 700 | 700 | 700 | 700 | 700 | 700 | 700 | 700 | 700 | 700 | 700 | 700 | 700 |

Missing catalog numbers available upon request.

DRIPPERLINES TECHNICAL DATA

| MODEL | INSIDE DIAMETER (MM) | WALL THICKNESS (MM) | OUTSIDE DIAMETER (MM) | MAX. WORKING PRESSURE (BAR) | MAXIMUM FLUSHING PRESSURE (BAR) | KD |
|-------|----------------------|---------------------|-----------------------|-----------------------------|---------------------------------|------|
| 12150 | 11.80 | 0.38 | 12.56 | 3.0 | 3.5 | 1.35 |

DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

| MODEL | WALL THICKNESS (MM) | DISTANCE BETWEEN DRIPPERS (M) | COIL LENGTH (M) | AVERAGE* COIL WEIGHT (KG) | COILS PER PALLET (UNITS) | COILS IN A 40 FEET CONTAINER (UNITS) | TOTAL IN A 40 FEET CONTAINER (M) |
|-------|---------------------|-------------------------------|-----------------|---------------------------|--------------------------|--------------------------------------|----------------------------------|
| 12150 | 0.38 | 0.15 to 0.19 | 600 | 11.1 | 12 | 480 | 288000 |
| | | 0.20 to 0.35 | 700 | 11.3 | | | 336000 |
| | | 0.40 to 1.00 | 700 | 10.9 | | | 336000 |

*According to drippers spacing

DRIPNET PC™ AS 12200

Catalog number **17245** - (any of below 6 digits)

| FLOW RATE (L/H) | DISTANCE BETWEEN DRIPPERS (M) | | | | | | | | | | | | | |
|------------------------|-------------------------------|------|------|--------|------|--------|------|------|------|------|------|------|------|------|
| | 0.15 | 0.20 | 0.25 | 0.30 | 0.35 | 0.40 | 0.50 | 0.60 | 0.65 | 0.70 | 0.75 | 0.80 | 0.90 | 1.00 |
| 0.6 | | | | 001370 | | 001470 | | | | | | | | |
| 1.0 | | | | 002470 | | 002570 | | | | | | | | |
| 1.6 | | | | 003470 | | 003570 | | | | | | | | |
| 2.0 | | | | | | | | | | | | | | |
| 3.0 | | | | | | | | | | | | | | |
| 3.8 | | | | | | | | | | | | | | |
| Carton coil length (m) | 650 | 750 | 750 | 750 | 750 | 850 | 850 | 850 | 850 | 850 | 850 | 850 | 850 | 850 |

Missing catalog numbers available upon request.

DRIPPERLINES TECHNICAL DATA

| MODEL | INSIDE DIAMETER (MM) | WALL THICKNESS (MM) | OUTSIDE DIAMETER (MM) | MAX. WORKING PRESSURE (BAR)* | MAXIMUM FLUSHING PRESSURE (BAR) | KD |
|-------|----------------------|---------------------|-----------------------|------------------------------|---------------------------------|------|
| 12200 | 11.80 | 0.50 | 12.80 | 3.0 | 3.9 | 1.35 |

*Maximum working pressure is defined by the dripper and not by the dripperline wall thickness

DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

| MODEL | WALL THICKNESS (MM) | DISTANCE BETWEEN DRIPPERS (M) | COIL LENGTH (M) | AVERAGE* COIL WEIGHT (KG) | COILS PER PALLET (UNITS) | COILS IN A 40 FEET CONTAINER (UNITS) | TOTAL IN A 40 FEET CONTAINER (M) |
|-------|---------------------|-------------------------------|-----------------|---------------------------|--------------------------|--------------------------------------|----------------------------------|
| 12200 | 0.50 | 0.15 to 0.19 | 650 | 14.9 | 12 | 480 | 312000 |
| | | 0.20 to 0.35 | 750 | 15.4 | | | 360000 |
| | | 0.40 to 1.00 | 850 | 17.4 | | | 408000 |

*According to drippers spacing

DRIPNET PC™ AS 12250

Catalog number **17270** - (any of below 6 digits)

| FLOW RATE (L/H) | DISTANCE BETWEEN DRIPPERS (M) | | | | | | | | | | | | | |
|------------------------|-------------------------------|------|--------|--------|------|--------|--------|------|------|------|------|--------|------|------|
| | 0.15 | 0.20 | 0.25 | 0.30 | 0.35 | 0.40 | 0.50 | 0.60 | 0.65 | 0.70 | 0.75 | 0.80 | 0.90 | 1.00 |
| 0.6 | | | 001400 | 001520 | | 001630 | | | | | | | | |
| 1.0 | 002740 | | 002820 | 002920 | | 003030 | | | | | | | | |
| 1.6 | | | | 004100 | | 004220 | 004350 | | | | | 005100 | | |
| 2.0 | | | | | | | | | | | | | | |
| 3.0 | | | | | | | | | | | | | | |
| 3.8 | | | | | | | | | | | | | | |
| Carton coil length (m) | 600 | 700 | 700 | 700 | 700 | 800 | 800 | 800 | 800 | 800 | 800 | 800 | 800 | 800 |

Missing catalog numbers available upon request.

DRIPPERLINES TECHNICAL DATA

| MODEL | INSIDE DIAMETER (MM) | WALL THICKNESS (MM) | OUTSIDE DIAMETER (MM) | MAX. WORKING PRESSURE (BAR)* | MAXIMUM FLUSHING PRESSURE (BAR) | KD |
|-------|----------------------|---------------------|-----------------------|------------------------------|---------------------------------|------|
| 12250 | 11.80 | 0.63 | 13.06 | 3.0 | 3.9 | 1.35 |

*Maximum working pressure is defined by the dripper and not by the dripperline wall thickness

DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

| MODEL | WALL THICKNESS (MM) | DISTANCE BETWEEN DRIPPERS (M) | COIL LENGTH (M) | AVERAGE* COIL WEIGHT (KG) | COILS PER PALLET (UNITS) | COILS IN A 40 FEET CONTAINER (UNITS) | TOTAL IN A 40 FEET CONTAINER (M) |
|-------|---------------------|-------------------------------|-----------------|---------------------------|--------------------------|--------------------------------------|----------------------------------|
| 12250 | 0.63 | 0.15 to 0.19 | 600 | 16.7 | 12 | 480 | 288000 |
| | | 0.20 to 0.35 | 700 | 17.8 | | | 336000 |
| | | 0.40 to 1.00 | 800 | 19.9 | | | 384000 |

*According to drippers spacing

DRIPNET PC™ AS 16125

Catalog number **17610** - (any of below 6 digits)

| FLOW RATE (L/H) | DISTANCE BETWEEN DRIPPERS (M) | | | | | | | | | | | | | |
|------------------------|-------------------------------|--------|------|--------|------|--------|--------|--------|------|------|------|------|------|------|
| | 0.15 | 0.20 | 0.25 | 0.30 | 0.35 | 0.40 | 0.50 | 0.60 | 0.65 | 0.70 | 0.75 | 0.80 | 0.90 | 1.00 |
| 0.6 | | | | 000480 | | 000530 | 000740 | 000830 | | | | | | |
| 1.0 | | 001580 | | 001690 | | 001820 | 001920 | 002030 | | | | | | |
| 1.6 | | | | | | 003630 | 003730 | | | | | | | |
| 2.0 | | | | | | | | | | | | | | |
| 3.0 | | | | | | | | | | | | | | |
| 3.8 | | | | | | | | | | | | | | |
| Carton coil length (m) | 1150 | 1300 | 1300 | 1300 | 1300 | 1500 | 1500 | 1500 | 1500 | 1500 | 1500 | 1500 | 1500 | 1500 |

Missing catalog numbers available upon request.

DRIPPERLINES TECHNICAL DATA

| MODEL | INSIDE DIAMETER (MM) | WALL THICKNESS (MM) | OUTSIDE DIAMETER (MM) | MAX. WORKING PRESSURE (BAR) | MAXIMUM FLUSHING PRESSURE (BAR) | KD |
|-------|----------------------|---------------------|-----------------------|-----------------------------|---------------------------------|-----|
| 16125 | 16.20 | 0.31 | 16.82 | 1.8 | 2.1 | 0.4 |

DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

| MODEL | WALL THICKNESS (MM) | DISTANCE BETWEEN DRIPPERS (M) | COIL LENGTH (M) | AVERAGE* COIL WEIGHT (KG) | COILS PER PALLET (UNITS) | COILS IN A 40 FEET CONTAINER (UNITS) | TOTAL IN A 40 FEET CONTAINER (M) |
|-------|---------------------|-------------------------------|-----------------|---------------------------|--------------------------|--------------------------------------|----------------------------------|
| 16125 | 0.31 | 0.15 to 0.19 | 1150 | 24.0 | 12 | 480 | 552000 |
| | | 0.20 to 0.35 | 1300 | 23.9 | | | 624000 |
| | | 0.40 to 1.00 | 1500 | 26.5 | | | 720000 |

*According to drippers spacing

DRIPNET PC™ AS 16150

Catalog number **17615** - (any of below 6 digits)

| FLOW RATE (L/H) | DISTANCE BETWEEN DRIPPERS (M) | | | | | | | | | | | | | |
|------------------------|-------------------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|------|------|------|
| | 0.15 | 0.20 | 0.25 | 0.30 | 0.35 | 0.40 | 0.50 | 0.60 | 0.65 | 0.70 | 0.75 | 0.80 | 0.90 | 1.00 |
| 0.6 | | 000470 | 000495 | 000580 | | 000634 | 000672 | 000697 | | | | | | |
| 1.0 | 001370 | 001470 | 001482 | 001600 | 001580 | 001825 | 002015 | 002120 | 002210 | 002360 | | | | |
| 1.6 | | 004320 | | 004380 | 004520 | 004645 | 004820 | 004920 | 005020 | | 005120 | | | |
| 2.0 | | 007170 | | | | 007460 | | | | | | | | |
| 3.0 | | | | | | | | | | | | | | |
| 3.8 | | | | | | | | | | | | | | |
| Carton coil length (m) | 900 | 1000 | 1000 | 1000 | 1000 | 1200 | 1200 | 1200 | 1200 | 1200 | 1200 | 1200 | 1200 | 1200 |

Missing catalog numbers available upon request.

DRIPPERLINES TECHNICAL DATA

| MODEL | INSIDE DIAMETER (MM) | WALL THICKNESS (MM) | OUTSIDE DIAMETER (MM) | MAX. WORKING PRESSURE (BAR) | MAXIMUM FLUSHING PRESSURE (BAR) | KD |
|-------|----------------------|---------------------|-----------------------|-----------------------------|---------------------------------|-----|
| 16150 | 16.20 | 0.38 | 16.96 | 2.2 | 2.5 | 0.4 |

DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

| MODEL | WALL THICKNESS (MM) | DISTANCE BETWEEN DRIPPERS (M) | COIL LENGTH (M) | AVERAGE* COIL WEIGHT (KG) | COILS PER PALLET (UNITS) | COILS IN A 40 FEET CONTAINER (UNITS) | TOTAL IN A 40 FEET CONTAINER (M) |
|-------|---------------------|-------------------------------|-----------------|---------------------------|--------------------------|--------------------------------------|----------------------------------|
| 16150 | 0.38 | 0.15 to 0.19 | 900 | 21.2 | 12 | 480 | 432000 |
| | | 0.20 to 0.35 | 1000 | 21.1 | | | 480000 |
| | | 0.40 to 1.00 | 1200 | 25.6 | | | 576000 |

*According to drippers spacing

DRIPNET PC™ AS 16200

Catalog number **17635** - (any of below 6 digits)

| FLOW RATE (L/H) | DISTANCE BETWEEN DRIPPERS (M) | | | | | | | | | | | | | |
|------------------------|-------------------------------|--------|------|--------|------|--------|------|--------|------|------|------|------|------|------|
| | 0.15 | 0.20 | 0.25 | 0.30 | 0.35 | 0.40 | 0.50 | 0.60 | 0.65 | 0.70 | 0.75 | 0.80 | 0.90 | 1.00 |
| 0.6 | 001050 | 001110 | | 001250 | | | | | | | | | | |
| 1.0 | | | | 002400 | | 002600 | | | | | | | | |
| 1.6 | | | | | | | | 004550 | | | | | | |
| 2.0 | | | | | | | | | | | | | | |
| 3.0 | | | | | | | | | | | | | | |
| 3.8 | | | | | | | | | | | | | | |
| Carton coil length (m) | 750 | 800 | 800 | 800 | 800 | 850 | 850 | 850 | 850 | 850 | 850 | 850 | 850 | 850 |

Missing catalog numbers available upon request.

DRIPPERLINES TECHNICAL DATA

| MODEL | INSIDE DIAMETER (MM) | WALL THICKNESS (MM) | OUTSIDE DIAMETER (MM) | MAX. WORKING PRESSURE (BAR) | MAXIMUM FLUSHING PRESSURE (BAR) | KD |
|-------|----------------------|---------------------|-----------------------|-----------------------------|---------------------------------|-----|
| 16200 | 15.50 | 0.50 | 16.50 | 2.5 | 3.3 | 0.4 |

DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

| MODEL | WALL THICKNESS (MM) | DISTANCE BETWEEN DRIPPERS (M) | COIL LENGTH (M) | AVERAGE* COIL WEIGHT (KG) | COILS PER PALLET (UNITS) | COILS IN A 40 FEET CONTAINER (UNITS) | TOTAL IN A 40 FEET CONTAINER (M) |
|-------|---------------------|-------------------------------|-----------------|---------------------------|--------------------------|--------------------------------------|----------------------------------|
| 16200 | 0.50 | 0.15 to 0.19 | 750 | 19.9 | 12 | 480 | 360000 |
| | | 0.20 to 0.35 | 800 | 19.6 | | | 384000 |
| | | 0.40 to 1.00 | 850 | 19.1 | | | 408000 |

*According to drippers spacing

DRIPNET PC™ AS 16250

Catalog number **17645** - (any of below 6 digits)

| FLOW RATE (L/H) | DISTANCE BETWEEN DRIPPERS (M) | | | | | | | | | | | | | |
|------------------------|-------------------------------|------|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|------|--------|
| | 0.15 | 0.20 | 0.25 | 0.30 | 0.35 | 0.40 | 0.50 | 0.60 | 0.65 | 0.70 | 0.75 | 0.80 | 0.90 | 1.00 |
| 0.6 | | | | 001300 | | 001400 | 001500 | 001600 | | | 001620 | | | |
| 1.0 | 002490 | | | 002600 | 002650 | 002800 | 003100 | 003200 | 003250 | 003280 | 003300 | | | 003350 |
| 1.6 | | | | 004400 | 004500 | 004600 | 004800 | 005000 | 005100 | 005200 | 005300 | 005400 | | |
| 2.0 | | | | 006050 | | 006060 | 006100 | 006250 | | | | | | |
| 3.0 | | | | 007000 | | 007200 | 007400 | 007600 | 007620 | | 007700 | 007800 | | |
| 3.8 | | | | | | | 009000 | | | | | | | |
| Carton coil length (m) | 700 | 800 | 800 | 800 | 800 | 800 | 800 | 800 | 800 | 800 | 800 | 800 | 800 | 800 |

Missing catalog numbers available upon request.

DRIPPERLINES TECHNICAL DATA

| MODEL | INSIDE DIAMETER (MM) | WALL THICKNESS (MM) | OUTSIDE DIAMETER (MM) | MAX. WORKING PRESSURE (BAR) | MAXIMUM FLUSHING PRESSURE (BAR) | KD |
|-------|----------------------|---------------------|-----------------------|-----------------------------|---------------------------------|-----|
| 16250 | 15.50 | 0.63 | 16.76 | 2.8 | 3.6 | 0.4 |

DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

| MODEL | WALL THICKNESS (MM) | DISTANCE BETWEEN DRIPPERS (M) | COIL LENGTH (M) | AVERAGE* COIL WEIGHT (KG) | COILS PER PALLET (UNITS) | COILS IN A 40 FEET CONTAINER (UNITS) | TOTAL IN A 40 FEET CONTAINER (M) |
|-------|---------------------|-------------------------------|-----------------|---------------------------|--------------------------|--------------------------------------|----------------------------------|
| 16250 | 0.63 | 0.15 to 0.19 | 700 | 26.5 | 12 | 480 | 336000 |
| | | 0.20 to 0.35 | 800 | 26.9 | | | 384000 |
| | | 0.40 to 1.00 | 800 | 26.1 | | | 384000 |

*According to drippers spacing

DRIPNET PC™ AS 22135

Catalog number **17745** - (any of below 6 digits)

| FLOW RATE (L/H) | DISTANCE BETWEEN DRIPPERS (M) | | | | | | | | | | | | | |
|------------------------|-------------------------------|--------|------|--------|------|--------|--------|--------|------|------|------|------|------|------|
| | 0.15 | 0.20 | 0.25 | 0.30 | 0.35 | 0.40 | 0.50 | 0.60 | 0.65 | 0.70 | 0.75 | 0.80 | 0.90 | 1.00 |
| 0.6 | | 001200 | | 001310 | | | | | | | | | | |
| 1.0 | | | | | | 002550 | 002750 | 002850 | | | | | | |
| 1.6 | | | | | | 004650 | 004950 | | | | | | | |
| 2.0 | | | | | | | 006300 | | | | | | | |
| 3.0 | | | | | | | | | | | | | | |
| 3.8 | | | | | | | | | | | | | | |
| Carton coil length (m) | 750 | 800 | 800 | 800 | 800 | 950 | 950 | 950 | 950 | 950 | 950 | 950 | 950 | 950 |

Missing catalog numbers available upon request.

DRIPPERLINES TECHNICAL DATA

| MODEL | INSIDE DIAMETER (MM) | WALL THICKNESS (MM) | OUTSIDE DIAMETER (MM) | MAX. WORKING PRESSURE (BAR) | MAXIMUM FLUSHING PRESSURE (BAR) | KD |
|-------|----------------------|---------------------|-----------------------|-----------------------------|---------------------------------|------|
| 22135 | 22.20 | 0.34 | 22.88 | 1.5 | 1.7 | 0.18 |

DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

| MODEL | WALL THICKNESS (MM) | DISTANCE BETWEEN DRIPPERS (M) | COIL LENGTH (M) | AVERAGE* COIL WEIGHT (KG) | COILS PER PALLET (UNITS) | COILS IN A 40 FEET CONTAINER (UNITS) | TOTAL IN A 40 FEET CONTAINER (M) |
|-------|---------------------|-------------------------------|-----------------|---------------------------|--------------------------|--------------------------------------|----------------------------------|
| 22135 | 0.34 | 0.15 to 0.19 | 750 | 22.1 | 12 | 480 | 360000 |
| | | 0.20 to 0.35 | 800 | 21.6 | | | 384000 |
| | | 0.40 to 1.00 | 950 | 24.5 | | | 456000 |

*According to drippers spacing

DRIPNET PC™ AS 22150

Catalog number **17770** - (any of below 6 digits)

| FLOW RATE (L/H) | DISTANCE BETWEEN DRIPPERS (M) | | | | | | | | | | | | | |
|------------------------|-------------------------------|--------|--------|------|------|--------|--------|--------|------|------|------|------|------|------|
| | 0.15 | 0.20 | 0.25 | 0.30 | 0.35 | 0.40 | 0.50 | 0.60 | 0.65 | 0.70 | 0.75 | 0.80 | 0.90 | 1.00 |
| 0.6 | | 001470 | 001600 | | | 001850 | 002050 | 002070 | | | | | | |
| 1.0 | | 003740 | | | | 003850 | 004020 | 004150 | | | | | | |
| 1.6 | | 004900 | | | | 005070 | 005170 | 005250 | | | | | | |
| 2.0 | | | | | | | 006170 | | | | | | | |
| 3.0 | | | | | | | | | | | | | | |
| 3.8 | | | | | | | | | | | | | | |
| Carton coil length (m) | 650 | 750 | 750 | 750 | 750 | 850 | 850 | 850 | 850 | 850 | 850 | 850 | 850 | 850 |

Missing catalog numbers available upon request.

DRIPPERLINES TECHNICAL DATA

| MODEL | INSIDE DIAMETER (MM) | WALL THICKNESS (MM) | OUTSIDE DIAMETER (MM) | MAX. WORKING PRESSURE (BAR) | MAXIMUM FLUSHING PRESSURE (BAR) | KD |
|-------|----------------------|---------------------|-----------------------|-----------------------------|---------------------------------|------|
| 22150 | 22.20 | 0.38 | 22.96 | 1.8 | 2.1 | 0.18 |

DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

| MODEL | WALL THICKNESS (MM) | DISTANCE BETWEEN DRIPPERS (M) | COIL LENGTH (M) | AVERAGE* COIL WEIGHT (KG) | COILS PER PALLET (UNITS) | COILS IN A 40 FEET CONTAINER (UNITS) | TOTAL IN A 40 FEET CONTAINER (M) |
|-------|---------------------|-------------------------------|-----------------|---------------------------|--------------------------|--------------------------------------|----------------------------------|
| 22150 | 0.38 | 0.15 to 0.19 | 650 | 21.1 | 12 | 480 | 312000 |
| | | 0.20 to 0.35 | 750 | 22.4 | | | 360000 |
| | | 0.40 to 1.00 | 850 | 24.4 | | | 408000 |

*According to drippers spacing

DRIPNET PC™ AS 22250

Catalog number **17790** - (any of below 6 digits)

| FLOW RATE (L/H) | DISTANCE BETWEEN DRIPPERS (M) | | | | | | | | | | | | | |
|------------------------|-------------------------------|--------|--------|--------|------|--------|--------|--------|------|------|------|------|------|------|
| | 0.15 | 0.20 | 0.25 | 0.30 | 0.35 | 0.40 | 0.50 | 0.60 | 0.65 | 0.70 | 0.75 | 0.80 | 0.90 | 1.00 |
| 0.6 | | | | 001700 | | 001800 | 002000 | | | | | | | |
| 1.0 | | | | 003650 | | 003800 | 004000 | 004040 | | | | | | |
| 1.6 | | 004850 | | | | 004950 | 005050 | | | | | | | |
| 2.0 | | | | | | | 006050 | | | | | | | |
| 3.0 | | | 007500 | | | | | | | | | | | |
| 3.8 | | | | | | | | | | | | | | |
| Carton coil length (m) | 450 | 500 | 500 | 500 | 500 | 500 | 500 | 500 | 500 | 500 | 500 | 500 | 500 | 500 |

Missing catalog numbers available upon request.

DRIPPERLINES TECHNICAL DATA

| MODEL | INSIDE DIAMETER (MM) | WALL THICKNESS (MM) | OUTSIDE DIAMETER (MM) | MAX. WORKING PRESSURE (BAR) | MAXIMUM FLUSHING PRESSURE (BAR) | KD |
|-------|----------------------|---------------------|-----------------------|-----------------------------|---------------------------------|------|
| 22250 | 22.20 | 0.63 | 23.46 | 2.5 | 2.9 | 0.18 |

DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

| MODEL | WALL THICKNESS (MM) | DISTANCE BETWEEN DRIPPERS (M) | COIL LENGTH (M) | AVERAGE* COIL WEIGHT (KG) | COILS PER PALLET (UNITS) | COILS IN A 40 FEET CONTAINER (UNITS) | TOTAL IN A 40 FEET CONTAINER (M) |
|-------|---------------------|-------------------------------|-----------------|---------------------------|--------------------------|--------------------------------------|----------------------------------|
| 22250 | 0.63 | 0.15 to 0.19 | 450 | 26.6 | 12 | 480 | 216000 |
| | | 0.20 to 0.35 | 500 | 28.0 | | | 240000 |
| | | 0.40 to 1.00 | 500 | 27.4 | | | 240000 |

*According to drippers spacing

DRIPNET PC™ AS 25135

Catalog number **17815** - (any of below 6 digits)

| FLOW RATE (L/H) | DISTANCE BETWEEN DRIPPERS (M) | | | | | | | | | | | | | |
|------------------------|-------------------------------|------|------|--------|------|--------|------|------|------|------|------|------|------|------|
| | 0.15 | 0.20 | 0.25 | 0.30 | 0.35 | 0.40 | 0.50 | 0.60 | 0.65 | 0.70 | 0.75 | 0.80 | 0.90 | 1.00 |
| 0.6 | | | | 001500 | | 001600 | | | | | | | | |
| 1.0 | | | | | | 002600 | | | | | | | | |
| 1.6 | | | | | | | | | | | | | | |
| 2.0 | | | | | | | | | | | | | | |
| 3.0 | | | | | | | | | | | | | | |
| 3.8 | | | | | | | | | | | | | | |
| Carton coil length (m) | 550 | 700 | 700 | 700 | 700 | 700 | 700 | 700 | 700 | 700 | 700 | 700 | 700 | 700 |

Missing catalog numbers available upon request.

DRIPPERLINES TECHNICAL DATA

| MODEL | INSIDE DIAMETER (MM) | WALL THICKNESS (MM) | OUTSIDE DIAMETER (MM) | MAX. WORKING PRESSURE (BAR) | MAXIMUM FLUSHING PRESSURE (BAR) | KD |
|-------|----------------------|---------------------|-----------------------|-----------------------------|---------------------------------|------|
| 25135 | 25.00 | 0.34 | 25.68 | 1.2 | 1.4 | 0.04 |

DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

| MODEL | WALL THICKNESS (MM) | DISTANCE BETWEEN DRIPPERS (M) | COIL LENGTH (M) | AVERAGE* COIL WEIGHT (KG) | COILS PER PALLET (UNITS) | COILS IN A 40 FEET CONTAINER (UNITS) | TOTAL IN A 40 FEET CONTAINER (M) |
|-------|---------------------|-------------------------------|-----------------|---------------------------|--------------------------|--------------------------------------|----------------------------------|
| 25135 | 0.34 | 0.15 to 0.19 | 550 | 16.7 | 12 | 480 | 264000 |
| | | 0.20 to 0.35 | 700 | 19.6 | | | 336000 |
| | | 0.40 to 1.00 | 700 | 19.2 | | | 336000 |

*According to drippers spacing

DRIPNET PC™ AS 25150

Catalog number **17819** - (any of below 6 digits)

| FLOW RATE (L/H) | DISTANCE BETWEEN DRIPPERS (M) | | | | | | | | | | | | | |
|------------------------|-------------------------------|------|------|------|------|------|--------|------|------|------|------|------|------|------|
| | 0.15 | 0.20 | 0.25 | 0.30 | 0.35 | 0.40 | 0.50 | 0.60 | 0.65 | 0.70 | 0.75 | 0.80 | 0.90 | 1.00 |
| 0.6 | | | | | | | | | | | | | | |
| 1.0 | | | | | | | 002000 | | | | | | | |
| 1.6 | | | | | | | | | | | | | | |
| 2.0 | | | | | | | | | | | | | | |
| 3.0 | | | | | | | | | | | | | | |
| 3.8 | | | | | | | | | | | | | | |
| Carton coil length (m) | 450 | 600 | 600 | 600 | 600 | 600 | 600 | 600 | 600 | 600 | 600 | 600 | 600 | 600 |

Missing catalog numbers available upon request.

DRIPPERLINES TECHNICAL DATA

| MODEL | INSIDE DIAMETER (MM) | WALL THICKNESS (MM) | OUTSIDE DIAMETER (MM) | MAX. WORKING PRESSURE (BAR) | MAXIMUM FLUSHING PRESSURE (BAR) | KD |
|-------|----------------------|---------------------|-----------------------|-----------------------------|---------------------------------|------|
| 25150 | 25.00 | 0.38 | 25.76 | 1.4 | 1.6 | 0.04 |

DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

| MODEL | WALL THICKNESS (MM) | DISTANCE BETWEEN DRIPPERS (M) | COIL LENGTH (M) | AVERAGE* COIL WEIGHT (KG) | COILS PER PALLET (UNITS) | COILS IN A 40 FEET CONTAINER (UNITS) | TOTAL IN A 40 FEET CONTAINER (M) |
|-------|---------------------|-------------------------------|-----------------|---------------------------|--------------------------|--------------------------------------|----------------------------------|
| 25150 | 0.38 | 0.15 to 0.19 | 450 | 15.0 | 12 | 480 | 216000 |
| | | 0.20 to 0.35 | 600 | 18.7 | | | 288000 |
| | | 0.40 to 1.00 | 600 | 18.3 | | | 288000 |

*According to drippers spacing

DRIPNET PC™ AS 25250

Catalog number **17850** - (any of below 6 digits)

| FLOW RATE (L/H) | DISTANCE BETWEEN DRIPPERS (M) | | | | | | | | | | | | | |
|------------------------|-------------------------------|------|------|--------|------|------|--------|--------|------|------|------|------|------|------|
| | 0.15 | 0.20 | 0.25 | 0.30 | 0.35 | 0.40 | 0.50 | 0.60 | 0.65 | 0.70 | 0.75 | 0.80 | 0.90 | 1.00 |
| 0.6 | | | | 001600 | | | 001720 | 001800 | | | | | | |
| 1.0 | | | | 002500 | | | 002700 | 002850 | | | | | | |
| 1.6 | | | | | | | 003850 | | | | | | | |
| 2.0 | | | | | | | | | | | | | | |
| 3.0 | | | | | | | | | | | | | | |
| 3.8 | | | | | | | | | | | | | | |
| Carton coil length (m) | 450 | 500 | 500 | 500 | 500 | 500 | 500 | 500 | 500 | 500 | 500 | 500 | 500 | 500 |

Missing catalog numbers available upon request.

DRIPPERLINES TECHNICAL DATA

| MODEL | INSIDE DIAMETER (MM) | WALL THICKNESS (MM) | OUTSIDE DIAMETER (MM) | MAX. WORKING PRESSURE (BAR) | MAXIMUM FLUSHING PRESSURE (BAR) | KD |
|-------|----------------------|---------------------|-----------------------|-----------------------------|---------------------------------|------|
| 25250 | 25.00 | 0.63 | 26.26 | 2.0 | 2.3 | 0.04 |

DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

| MODEL | WALL THICKNESS (MM) | DISTANCE BETWEEN DRIPPERS (M) | COIL LENGTH (M) | AVERAGE* COIL WEIGHT (KG) | COILS PER PALLET (UNITS) | COILS IN A 40 FEET CONTAINER (UNITS) | TOTAL IN A 40 FEET CONTAINER (M) |
|-------|---------------------|-------------------------------|-----------------|---------------------------|--------------------------|--------------------------------------|----------------------------------|
| 25250 | 0.63 | 0.15 to 0.19 | 450 | 20.9 | 12 | 480 | 216000 |
| | | 0.20 to 0.35 | 500 | 25.0 | | | 240000 |
| | | 0.40 to 1.00 | 500 | 24.7 | | | 240000 |

*According to drippers spacing

NETAFIM AUSTRALIA

P: 1300 307 407
 E: au.net.info@netafim.com
 W: netafim.com.au



DripNet PC AS MWD Dripline
 September 2017
 CP

