



## TYPHOON PLUS™

INTEGRAL DRIPPER

12080 - 12100 - 12125 - 12150 - 16080- 16100 - 16125 - 16150 - 22080  
22100 - 22125 - 22135 - 22150 - 25080 - 25100 - 25125 - 25135 - 25150

### APPLICATIONS

- Row crops and vegetables, multi seasonal irrigation.
- On or Semi permanent sub surface installations.

### BENEFITS AND FEATURES

#### High & uniform yield year after year

- Innovative labyrinth -TurbuNext™ - with wide water passages, large deep and wide cross section, allows usage of harsh water while using regular filtration technologies.
- Wide filtration area that ensures optimal performance even under harsh water conditions.  
The unique innovative labyrinth -TurbuNext™, with the wide filtration area allows reducing filtration requirements resulting in higher flushing efficiency flushing, and waste of water and energy.
- Unique filter design, the water is drawn in to the dripper near the stream center, that prevents the entrance of sediments into the drippers.
- Typhoon Plus's exponent X is 0.45 meaning low variation between drippers along the lateral resulting in more uniform yield

#### Reliability & confidence

- The Typhoon Plus™ is manufactured according to the highest levels of quality control and assurance.  
Complying with International Standard ISO 9261.
- Injection molded dripper construction, ensuring uniform drippers and very low CV.

### SPECIFICATIONS

- 5 different flow rates.
- Maximum system pressure: according to dripperlines diameters and wall thickness.
- Recommended filtration: according to dripper flow rate.  
Filtration method to be selected based on the kind and concentration of the contaminants existing in the water.  
Wherever sand exceeding 2 ppm exists in the water, a Hydrocyclon should be installed before the main filter.  
When sand / silt / clay exceed 100 ppm, pre-treatment should be applied according to Netafim™ expert team's instructions.
- Wide range of diameters and wall thicknesses.  
Diameter: from 12.0 to 25.0 mm.  
Wall thickness: from 0.20 to 0.40 mm (8 to 15 mil).
- Injected dripper, very low CV.
- High UV resistant.
- Resistant to standard nutrients used in agricultural.

### DRIPPERS TECHNICAL DATA

FLOW RATE* (L/H)	MAXIMUM WORKING PRESSURE** (BAR)	WATER PASSAGES DIMENSIONS WIDTH-DEPTH-LENGTH (MM)	FILTRATION AREA (MM²)	CONSTANT K	EXPONENT X	RECOMMENDED FILTRATION ( MICRON)/(MESH)
0.50	0.6 up to 3.0	0.45 x 0.45 x 34	21	0.177	0.45	130/120
0.70		0.52 x 0.51 x 34	22	0.247	0.45	130/120
1.00		0.60 x 0.59 x 34	24	0.355	0.45	200/80
1.60		0.66 x 0.63 x 18	24	0.567	0.45	200/80
2.20		0.77 x 0.72 x 18	24	0.780	0.45	200/80

\*Flow rate at 1.0 bar pressure \*\* According to dripperlines diameter and wall thickness

## TYPHOON PLUS™ 12125 (WITH HOLE OUTLET)

Catalog number **15686** - (any of below 6 digits)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.50														
0.70														
1.00				000100										
1.60				000130										
2.20														
Carton coils length (m)	1200	1200	1200	1300	1300	1300	1300	1300	1300	1300	1300	1300	1300	1300

Missing catalog numbers available upon request.

### DRIPPERLINES TECHNICAL DATA

MODEL	INSIDE DIAMETER (MM)	WALL THICKNESS (MM)	OUTSIDE DIAMETER (MM)	MAX. WORKING PRESSURE (BAR)	MAXIMUM FLUSHING PRESSURE (BAR)	KD
12125	11.80	0.31	12.42	2.5	2.9	0.20

### DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

MODEL	WALL THICKNESS (MM)	DISTANCE BETWEEN DRIPPERS (M)	COIL LENGTH (M)	AVERAGE* COIL WEIGHT (KG)	COILS PER PALLET (UNITS)	COILS IN A 40 FEET CONTAINER (UNITS)	TOTAL IN A 40 FEET CONTAINER (M)
12125	0.31	0.15 to 0.25	1200	15.6	16	640	768000
		0.30 to 1.00	1300	16.3			832000

\*According to drippers spacing

## TYPHOON PLUS™ 12150 (WITH HOLE OUTLET)

Catalog number **15688** - (any of below 6 digits)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.50														
0.70														
1.00		000100		000130										
1.60														
2.20														
Carton coils length (m)	1100	1100	1100	1100	1100	1100	1100	1100	1100	1100	1100	1100	1100	1100

Missing catalog numbers available upon request.

### DRIPPERLINES TECHNICAL DATA

MODEL	INSIDE DIAMETER (MM)	WALL THICKNESS (MM)	OUTSIDE DIAMETER (MM)	MAX. WORKING PRESSURE (BAR)	MAXIMUM FLUSHING PRESSURE (BAR)	KD
12150	11.80	0.38	12.56	3.0	3.5	0.20

### DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

MODEL	WALL THICKNESS (MM)	DISTANCE BETWEEN DRIPPERS (M)	COIL LENGTH (M)	AVERAGE* COIL WEIGHT (KG)	COILS PER PALLET (UNITS)	COILS IN A 40 FEET CONTAINER (UNITS)	TOTAL IN A 40 FEET CONTAINER (M)
12150	0.38	0.15 to 0.25	1100	17.2	16	640	704000
		0.30 to 1.00	1100	16.8			704000

\*According to drippers spacing

## TYPHOON PLUS™ 16080 (WITH FLAP OUTLET)

Catalog number **15690** - (any of below 6 digits)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.50														
0.70														
1.00				000160										
1.60		000490	000520											
2.20														
Carton coils length (m)	2400	2400	2400	2500	2500	2500	2500	2500	2500	2500	2500	2500	2500	2500

Missing catalog numbers available upon request.

## TYPHOON PLUS™ 16080 (WITH HOLE OUTLET)

Catalog number **15690** - (any of below 6 digits)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.50														
0.70														
1.00			000100	000130	000260	000140								
1.60		000460					000550							
2.20														
Carton coils length (m)	2400	2400	2400	2500	2500	2500	2500	2500	2500	2500	2500	2500	2500	2500

Missing catalog numbers available upon request.

## DRIPPERLINES TECHNICAL DATA

MODEL	INSIDE DIAMETER (MM)	WALL THICKNESS (MM)	OUTSIDE DIAMETER (MM)	MAX. WORKING PRESSURE (BAR)	MAXIMUM FLUSHING PRESSURE (BAR)	KD
16080	16.20	0.20	16.60	1.0	1.2	0.10

## DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

MODEL	WALL THICKNESS (MM)	DISTANCE BETWEEN DRIPPERS (M)	COIL LENGTH (M)	AVERAGE* COIL WEIGHT (KG)	COILS PER PALLET (UNITS)	COILS IN A 40 FEET CONTAINER (UNITS)	TOTAL IN A 40 FEET CONTAINER (M)
16080	0.20	0.15 to 0.25	2400	26.9	16	640	1536000
		0.30 to 1.00	2500	27.1			1600000

\*According to drippers spacing

## TYPHOON PLUS™ 16100 (WITH FLAP OUTLET)

Catalog number **15695** - (any of below 6 digits)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.50														
0.70														
1.00		000100	000130	000160	000220	000250								
1.60		000410		000470	000500	000560								
2.20														
Carton coils length (m)	1900	1900	1900	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000

Missing catalog numbers available upon request.

## TYPHOON PLUS™ 16100 (WITH HOLE OUTLET)

Catalog number **15695** - (any of below 6 digits)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.50														
0.70														
1.00					000190		000280							
1.60				000440		000530		000650						
2.20														
Carton coils length (m)	1900	1900	1900	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000

Missing catalog numbers available upon request.

## DRIPPERLINES TECHNICAL DATA

MODEL	INSIDE DIAMETER (MM)	WALL THICKNESS (MM)	OUTSIDE DIAMETER (MM)	MAX. WORKING PRESSURE (BAR)	MAXIMUM FLUSHING PRESSURE (BAR)	KD
16100	16.20	0.25	16.70	1.4	1.6	0.10

## DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

MODEL	WALL THICKNESS (MM)	DISTANCE BETWEEN DRIPPERS (M)	COIL LENGTH (M)	AVERAGE* COIL WEIGHT (KG)	COILS PER PALLET (UNITS)	COILS IN A 40 FEET CONTAINER (UNITS)	TOTAL IN A 40 FEET CONTAINER (M)
16100	0.25	0.15 to 0.25	1900	26.2	16	640	1216000
		0.30 to 1.00	2000	26.9			1280000

\*According to drippers spacing

## TYPHOON PLUS™ 16125 (WITH FLAP OUTLET)

Catalog number **15700** - (any of below 6 digits)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.50														
0.70				000100										
1.00		000230		000290		000350	000440							
1.60	000540			000630										
2.20														
Carton coils length (m)	1350	1350	1350	1600	1600	1600	1600	1600	1600	1600	1600	1600	1600	1600

Missing catalog numbers available upon request.

## TYPHOON PLUS™ 16125 (WITH HOLE OUTLET)

Catalog number **15700** - (any of below 6 digits)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.50														
0.70														
1.00		000200		000260	000320	000380	000410							
1.60			000600	000660		000690	000750							
2.20														
Carton coils length (m)	1350	1350	1350	1600	1600	1600	1600	1600	1600	1600	1600	1600	1600	1600

Missing catalog numbers available upon request.

## DRIPPERLINES TECHNICAL DATA

MODEL	INSIDE DIAMETER (MM)	WALL THICKNESS (MM)	OUTSIDE DIAMETER (MM)	MAX. WORKING PRESSURE (BAR)	MAXIMUM FLUSHING PRESSURE (BAR)	KD
16125	16.20	0.31	16.82	1.8	2.1	0.10

## DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

MODEL	WALL THICKNESS (MM)	DISTANCE BETWEEN DRIPPERS (M)	COIL LENGTH (M)	AVERAGE* COIL WEIGHT (KG)	COILS PER PALLET (UNITS)	COILS IN A 40 FEET CONTAINER (UNITS)	TOTAL IN A 40 FEET CONTAINER (M)
16125	0.31	0.15 to 0.25	1350	26.2	16	640	864000
		0.30 to 1.00	1600	26.5			1024000

\*According to drippers spacing

## TYPHOON PLUS™ 16150 (WITH FLAP OUTLET)

Catalog number **15705** - (any of below 6 digits)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.50														
0.70		000100		000130										
1.00				000290			000410							
1.60		000510		000540			000840	000940						
2.20														
Carton coils length (m)	1200	1200	1200	1300	1300	1300	1300	1300	1300	1300	1300	1300	1300	1300

Missing catalog numbers available upon request.

## TYPHOON PLUS™ 16150 (WITH HOLE OUTLET)

Catalog number **15705** - (any of below 6 digits)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.50														
0.70														
1.00		000230		000260	000320		000380							
1.60				000640										
2.20														
Carton coils length (m)	1200	1200	1200	1300	1300	1300	1300	1300	1300	1300	1300	1300	1300	1300

Missing catalog numbers available upon request.

## DRIPPERLINES TECHNICAL DATA

MODEL	INSIDE DIAMETER (MM)	WALL THICKNESS (MM)	OUTSIDE DIAMETER (MM)	MAX. WORKING PRESSURE (BAR)	MAXIMUM FLUSHING PRESSURE (BAR)	KD
16150	16.20	0.38	16.96	2.2	2.5	0.10

## DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

MODEL	WALL THICKNESS (MM)	DISTANCE BETWEEN DRIPPERS (M)	COIL LENGTH (M)	AVERAGE* COIL WEIGHT (KG)	COILS PER PALLET (UNITS)	COILS IN A 40 FEET CONTAINER (UNITS)	TOTAL IN A 40 FEET CONTAINER (M)
16150	0.38	0.15 to 0.25	1200	26.5	16	640	768000
		0.30 to 1.00	1300	26.0			832000

\*According to drippers spacing

## TYPHOON PLUS™ 22080 (WITH FLAP OUTLET)

Catalog number **15710** - (any of below 6 digits)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.50		001100												
0.70			001150	001250		001350	001450							
1.00		001600		001750		001850	001950							002100
1.60				002200		002300	002350							
2.20				002400										
Carton coils length (m)	1500	1500	1500	1700	1700	1700	1700	1700	1700	1700	1700	1700	1700	1700

Missing catalog numbers available upon request.

## TYPHOON PLUS™ 22080 (WITH HOLE OUTLET)

Catalog number **15710** - (any of below 6 digits)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.50														
0.70				001200		001300	001400	001500						
1.00		001560	001650	001700		001800	001900	002000						002050
1.60				002150		002250								
2.20							002450							
Carton coils length (m)	1500	1500	1500	1700	1700	1700	1700	1700	1700	1700	1700	1700	1700	1700

Missing catalog numbers available upon request.

## DRIPPERLINES TECHNICAL DATA

MODEL	INSIDE DIAMETER (MM)	WALL THICKNESS (MM)	OUTSIDE DIAMETER (MM)	MAX. WORKING PRESSURE (BAR)	MAXIMUM FLUSHING PRESSURE (BAR)	KD
22080	22.20	0.20	22.60	0.8	0.9	0.02

## DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

MODEL	WALL THICKNESS (MM)	DISTANCE BETWEEN DRIPPERS (M)	COIL LENGTH (M)	AVERAGE* COIL WEIGHT (KG)	COILS PER PALLET (UNITS)	COILS IN A 40 FEET CONTAINER (UNITS)	TOTAL IN A 40 FEET CONTAINER (M)
22080	0.20	0.15 to 0.25	1500	26.9	16	640	960000
		0.30 to 1.00	1700	27.6			1088000

\*According to drippers spacing

## TYPHOON PLUS™ 22100 (WITH FLAP OUTLET)

Catalog number **15715** - (any of below 6 digits)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.50														
0.70				001250		001350	001450	001550						
1.00		001600	001650	001750		001900	002000							
1.60				002200		002350	002500	002550						
2.20														
Carton coils length (m)	1200	1200	1200	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500

Missing catalog numbers available upon request.

## TYPHOON PLUS™ 22100 (WITH HOLE OUTLET)

Catalog number **15715** - (any of below 6 digits)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.50														
0.70				001200		001300	001400	001500						
1.00				001700	001800	001850	001950	002050						
1.60		002100		002150		002300	002450							
2.20				002650										
Carton coils length (m)	1200	1200	1200	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500

Missing catalog numbers available upon request.

## DRIPPERLINES TECHNICAL DATA

MODEL	INSIDE DIAMETER (MM)	WALL THICKNESS (MM)	OUTSIDE DIAMETER (MM)	MAX. WORKING PRESSURE (BAR)	MAXIMUM FLUSHING PRESSURE (BAR)	KD
22100	22.20	0.25	22.70	1.1	1.3	0.02

## DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

MODEL	WALL THICKNESS (MM)	DISTANCE BETWEEN DRIPPERS (M)	COIL LENGTH (M)	AVERAGE* COIL WEIGHT (KG)	COILS PER PALLET (UNITS)	COILS IN A 40 FEET CONTAINER (UNITS)	TOTAL IN A 40 FEET CONTAINER (M)
22100	0.25	0.15 to 0.25	1200	25.8	16	640	768000
		0.30 to 1.00	1500	27.1			960000

\*According to drippers spacing



## TYPHOON PLUS™ 22135 (WITH FLAP OUTLET)

Catalog number **15725** - (any of below 6 digits)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.50														
0.70				001250	001300	001400	001500	001550						
1.00		001650		001750	001800	001900	002050	002150	002200		002250			
1.60		002350	002450	002550		002650	002750	002850	002950	003000	003050			003200
2.20				003300		003400	003500	003600						
Carton coils length (m)	1100	1100	1100	1100	1100	1100	1100	1100	1100	1100	1100	1100	1100	1100

Missing catalog numbers available upon request.

## TYPHOON PLUS™ 22135 (WITH HOLE OUTLET)

Catalog number **15725** - (any of below 6 digits)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.50														
0.70			001150	001200		001350	001450							
1.00		001600		001700		001850	002000	002100						
1.60		002300	002400	002500		002600	002700	002800				003100		003150
2.20				003250		003350	003450	003550						
Carton coils length (m)	1100	1100	1100	1100	1100	1100	1100	1100	1100	1100	1100	1100	1100	1100

Missing catalog numbers available upon request.

## DRIPPERLINES TECHNICAL DATA

MODEL	INSIDE DIAMETER (MM)	WALL THICKNESS (MM)	OUTSIDE DIAMETER (MM)	MAX. WORKING PRESSURE (BAR)	MAXIMUM FLUSHING PRESSURE (BAR)	KD
22135	22.20	0.34	22.88	1.5	1.7	0.02

## DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

MODEL	WALL THICKNESS (MM)	DISTANCE BETWEEN DRIPPERS (M)	COIL LENGTH (M)	AVERAGE* COIL WEIGHT (KG)	COILS PER PALLET (UNITS)	COILS IN A 40 FEET CONTAINER (UNITS)	TOTAL IN A 40 FEET CONTAINER (M)
22135	0.34	0.15 to 0.25	1100	27.2	16	640	704000
		0.30 to 1.00	1100	26.8			704000

\*According to drippers spacing

## TYPHOON PLUS™ 22150 (WITH FLAP OUTLET)

Catalog number **15730** - (any of below 6 digits)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.50														
0.70				001250	001300	001400	001500	001550						
1.00		001600		001700	001800	001900	002000	002050	002100					
1.60	002150	002200	002250	002300	002350	002450	002500	002600	002650		002700			
2.20				002850		002900	002950	003000		003050				
Carton coils length (m)	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000

Missing catalog numbers available upon request.

## TYPHOON PLUS™ 22150 (WITH HOLE OUTLET)

Catalog number **15730** - (any of below 6 digits)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.50														
0.70				001200		001350	001450							
1.00				001650	001750	001850	001950							
1.60				002800		002400								
2.20														
Carton coils length (m)	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000

Missing catalog numbers available upon request.

## DRIPPERLINES TECHNICAL DATA

MODEL	INSIDE DIAMETER (MM)	WALL THICKNESS (MM)	OUTSIDE DIAMETER (MM)	MAX. WORKING PRESSURE (BAR)	MAXIMUM FLUSHING PRESSURE (BAR)	KD
22150	22.20	0.38	22.96	1.8	2.1	0.02

## DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

MODEL	WALL THICKNESS (MM)	DISTANCE BETWEEN DRIPPERS (M)	COIL LENGTH (M)	AVERAGE* COIL WEIGHT (KG)	COILS PER PALLET (UNITS)	COILS IN A 40 FEET CONTAINER (UNITS)	TOTAL IN A 40 FEET CONTAINER (M)
22150	0.38	0.15 to 0.25	1000	27.6	16	640	640000
		0.30 to 1.00	1000	27.2			640000

\*According to drippers spacing

## TYPHOON PLUS™ 25135 (WITH FLAP OUTLET)

Catalog number **15740** - (any of below 6 digits)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.50														
0.70				001200										
1.00						001250	001300							
1.60						001450	001500							
2.20														
Carton coils length (m)	900	900	900	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000

Missing catalog numbers available upon request.

## TYPHOON PLUS™ 25135 (WITH HOLE OUTLET)

Catalog number **15740** - (any of below 6 digits)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.50														
0.70														
1.00														
1.60				001350		001400								
2.20														
Carton coils length (m)	900	900	900	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000

Missing catalog numbers available upon request.

## DRIPPERLINES TECHNICAL DATA

MODEL	INSIDE DIAMETER (MM)	WALL THICKNESS (MM)	OUTSIDE DIAMETER (MM)	MAX. WORKING PRESSURE (BAR)	MAXIMUM FLUSHING PRESSURE (BAR)	KD
25135	25.00	0.34	25.68	1.2	1.4	0.01

## DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

MODEL	WALL THICKNESS (MM)	DISTANCE BETWEEN DRIPPERS (M)	COIL LENGTH (M)	AVERAGE* COIL WEIGHT (KG)	COILS PER PALLET (UNITS)	COILS IN A 40 FEET CONTAINER (UNITS)	TOTAL IN A 40 FEET CONTAINER (M)
25135	0.34	0.15 to 0.25	900	25.0	16	640	576000
		0.30 to 1.00	1000	27.3			640000

\*According to drippers spacing

## TYPHOON PLUS™ 25150 (WITH FLAP OUTLET)

Catalog number **15745** - (any of below 6 digits)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.50						000500								
0.70				001200										
1.00				001250		001300	001350	001400						
1.60							001450	001500						
2.20														
Carton coils length (m)	900	900	900	900	900	900	900	900	900	900	900	900	900	900

Missing catalog numbers available upon request.

## TYPHOON PLUS™ 25150 (WITH HOLE OUTLET)

Catalog number **15745** - (any of below 6 digits)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.50														
0.70														
1.00														
1.60														
2.20														
Carton coils length (m)	900	900	900	900	900	900	900	900	900	900	900	900	900	900

Missing catalog numbers available upon request.

## DRIPPERLINES TECHNICAL DATA

MODEL	INSIDE DIAMETER (MM)	WALL THICKNESS (MM)	OUTSIDE DIAMETER (MM)	MAX. WORKING PRESSURE (BAR)	MAXIMUM FLUSHING PRESSURE (BAR)	KD
25150	25.00	0.38	25.76	1.4	1.6	0.01

## DRIPPERLINES PACKAGE DATA (ON CARTON COILS)

MODEL	WALL THICKNESS (MM)	DISTANCE BETWEEN DRIPPERS (M)	COIL LENGTH (M)	AVERAGE* COIL WEIGHT (KG)	COILS PER PALLET (UNITS)	COILS IN A 40 FEET CONTAINER (UNITS)	TOTAL IN A 40 FEET CONTAINER (M)
25150	0.38	0.15 to 0.25	900	27.7	16	640	576000
		0.30 to 1.00	900	27.4			576000

\*According to drippers spacing